

## TABLE OF CONTENTS

<u>Section</u>		<u>Page</u>
<b>1.0</b>	<b><u>INTRODUCTION</u></b>	1-1
1.1	CREATION AND AUTHORITY OF THE DRAINAGE DISTRICT	1-2
1.2	PURPOSE	1-6
1.3	SCOPE	1-7
1.4	DRAINAGE POLICY	1-8
<b>2.0</b>	<b><u>HYDROLOGY</u></b>	2-1
2.1	GENERAL	2-1
2.2	RAINFALL – RUNOFF COMPUTATIONS USING HEC-HMS	2-3
2.2.1	<u>Design Storm Rainfall</u>	2-3
2.2.2	<u>Design Storm Losses</u>	2-4
2.2.3	<u>Design Storm Runoff</u>	2-6
2.2.3.1	General	2-6
2.2.3.2	Adjustment for Ponding	2-7
2.2.4	<u>Procedure for Developing a Design Runoff Hydrograph</u>	2-8
2.2.5	<u>Flood Routing</u>	2-12
2.3	DRAINAGE AREA-DISCHARGE CURVES	2-12
2.4	RATIONAL METHOD	2-13
2.4.1	<u>Runoff Coefficient (C)</u>	2-14
2.4.2	<u>Rainfall Intensity (i)</u>	2-15
2.4.3	<u>Drainage Area (A)</u>	2-17
2.5	HYDROGRAPH DEVELOPMENT FOR SMALL WATERSHEDS	2-17
<b>3.0</b>	<b><u>OPEN CHANNEL FLOW</u></b>	3-1
3.1	GENERAL	3-1
3.2	OPEN CHANNEL HYDRAULICS	3-1
3.2.1	<u>Steady or Unsteady Flow</u>	3-2
3.2.2	<u>Uniform Flow</u>	3-2
3.2.3	<u>Varied Flow</u>	3-3
3.2.4	<u>Subcritical or Supercritical Flow</u>	3-3
3.2.5	<u>Critical Depth</u>	3-3

<u>Section</u>		<u>Page</u>
3.2.6	<u>Manning's Equation</u>	3-4
3.2.6.1	Manning's "n" Value	3-5
3.3	CHANNEL DESIGN	3-6
3.3.1	<u>Design Frequency</u>	3-6
3.3.2	<u>Required Analysis</u>	3-6
3.3.3	<u>Design Considerations</u>	3-8
3.3.3.1	Optimal Design Flow Characteristics	3-8
3.3.3.2	Optimal Channel Configuration Characteristics	3-9
3.3.4	<u>Minimum Requirements for Channel Design</u>	3-11
3.3.4.1	Grass-Lined Channels	3-11
3.3.4.2	Concrete-Lined Trapezoidal Channels	3-12
3.3.4.3	Rectangular Concrete Pilot Channels	3-13
3.4	EROSION	3-14
3.4.1	<u>Minimum Erosion Protection Requirements</u>	3-15
3.4.2	<u>Structural Erosion Controls</u>	3-16
3.4.2.1	Riprap	3-16
3.4.2.2	Concrete Slope Paving	3-16
3.4.2.3	Backslope Drainage Systems	3-16
3.4.2.4	Slopes Drops	3-18
3.4.2.5	Baffled Chutes	3-18
3.5	WATER SURFACE PROFILES	3-20
3.5.1	<u>Uniform Flow</u>	3-20
3.5.2	<u>Gradually Varied Flow</u>	3-20
3.5.3	<u>Rapidly Varied Flow</u>	3-22
3.5.4	<u>Energy Losses</u>	3-22
3.5.4.1	Expansions and Contractions	3-22
3.5.4.2	Bends	3-23
3.5.4.3	Bridges	3-24
3.6	SUPERCritical TRANSITIONS	3-24
3.7	RIGHT-OF-WAY	3-24
3.8	UTILITY LINE CROSSINGS	3-25

<u>Section</u>		<u>Page</u>
<b>4.0</b>	<b><u>CULVERTS AND BRIDGES</u></b>	4-1
4.1	GENERAL	4-1
4.2	CULVERTS	4-1
4.2.1	<u>Design Frequency</u>	4-1
4.2.2	<u>Culvert Alignment</u>	4-1
4.2.3	<u>Culvert Length</u>	4-2
4.2.4	<u>Headwalls</u>	4-2
4.2.5	<u>Minimum Culvert Sizes</u>	4-2
4.2.6	<u>Manning's "n" Values</u>	4-2
4.2.7	<u>Erosion</u>	4-3
4.2.8	<u>Structural Requirements</u>	4-3
4.3	CULVERT HYDRAULIC DESIGN	4-4
4.3.1	<u>Culvert Design Procedure</u>	4-4
4.3.2	<u>Culvert Flow Types</u>	4-5
4.3.3	<u>Headwater Depth</u>	4-5
4.3.4	<u>Tailwater Depth</u>	4-5
4.3.5	<u>Inlet-Controlled Flow</u>	4-6
4.3.6	<u>Outlet-Controlled Flow</u>	4-6
4.3.7	<u>Conditions at Entrance</u>	4-9
4.3.8	<u>Step-by-Step Design Procedure</u>	4-9
4.4	BRIDGES	4-14
4.4.1	<u>Bridge Design Considerations</u>	4-14
4.4.1.1	Bents and Abutments	4-14
4.4.1.2	Interim Channels	4-15
4.4.1.3	Erosion Protection	4-15
4.5	HEC-RAS	4-15
<b>5.0</b>	<b><u>STORM SEWERS AND OVERLAND FLOW</u></b>	5-1
5.1	GENERAL	5-1
5.2	RUNOFF ANALYSIS	5-1
5.2.1	<u>Frequency Considerations</u>	5-1
5.2.2	<u>General Design Guidelines</u>	5-2
5.2.3	<u>Specific Design Flow Frequency Criteria</u>	5-3

<u>Section</u>		<u>Page</u>
5.3	STORM SEWERS	5-4
5.3.1	<u>Design Criteria</u>	5-4
5.3.2	<u>General Design Methodology</u>	5-7
5.3.3	<u>Head Losses</u>	5-7
5.3.3.1	Head Losses at Structures	5-7
5.3.3.2	Entrance Losses	5-8
5.3.4	<u>Manholes</u>	5-8
5.3.5	<u>Inlets</u>	5-8
5.3.5.1	Inlet Capacity	5-8
5.3.5.2	Inlet Spacing	5-9
5.4	STREET DRAINAGE OF STORM SEWER OVERFLOW	5-9
5.4.1	<u>Land Plan and Street Layout</u>	5-9
5.4.2	<u>Conveyance of Surface Flow to Primary Channels</u>	5-10
5.4.3	<u>Design Procedures for Pipe Outlet</u>	5-11
5.4.4	<u>Design Procedures for Extreme Event Swale</u>	5-14
5.4.5	<u>Roadside Ditch Drainage</u>	5-15
5.4.5.1	Preliminary Approval	5-15
5.4.5.2	Design Criteria	5-15
<b>6.0</b>	<b><u>STORM RUNOFF STORAGE</u></b>	6-1
6.1	GENERAL	6-1
6.2	MASTER PLANS	6-1
6.3	STORAGE CLASSIFICATION	6-2
6.3.1	<u>Retention Storage</u>	6-2
6.3.2	<u>Detention Storage</u>	6-2
6.3.3	<u>On-line Storage</u>	6-2
6.3.4	<u>Off-line Storage</u>	6-2
6.4	DESIGN PROCEDURES	6-3
6.4.1	<u>Design for Drainage Areas &lt;50 Acres</u>	6-3
6.4.2	<u>Design for Drainage ≥50 Acres and &lt;640 Acres</u>	6-5
6.4.3	<u>Design for Drainage Areas ≥640 Acres</u>	6-5
6.4.4	<u>Design Tailwater Depth</u>	6-6
6.4.5	<u>Release Rates / Maximum Allowable Discharge</u>	6-6

<u>Section</u>		<u>Page</u>
6.4.6	<u>Downstream Impact Analysis Requirements</u>	6-6
6.4.7	<u>Final Sizing of Pond Storage and Outflow Structures</u>	6-7
6.4.8	<u>Storm Sewer Hydraulic Gradients</u>	6-7
6.4.9	<u>Allowances for Extreme Storm Events</u>	6-7
6.4.10	<u>Erosion Controls</u>	6-8
6.5	MULTIPURPOSE LAND USE	6-9
6.5.1	<u>Approval of Private and Dual-Use Facilities</u>	6-10
6.5.2	<u>Maintenance</u>	6-10
6.6	PUMP DETENTION	6-12
6.7	GEOTECHNICAL INVESTIGATION	6-13
6.8	GENERAL REQUIREMENTS FOR DETENTION POND CONSTRUCTION	6-13
6.9	STORM WATER QUALITY BMP AND PHASE II NPDES PERMIT	6-14
6.10	LOW IMPACT DEVELOPMENT	6-15
<b>7.0</b>	<b><u>LEVEED AREAS</u></b>	7-1
7.1	INTERNAL DRAINAGE SYSTEM	7-1
7.2	LEVEE SYSTEM	7-1
7.2.1	<u>Frequency Criteria</u>	7-1
7.2.2	<u>Design Criteria</u>	7-2
7.3	PUMP STATION	7-6
7.3.1	<u>Frequency Criteria</u>	7-6
7.3.1.1	Design Criteria Assuming Coincidental Events	7-6
7.3.1.2	Design Criteria Assuming Same Event	7-7
7.3.2	<u>Design Criteria</u>	7-7
7.4	GRAVITY OUTLET AND OUTFALL CHANNEL	7-8
7.5	REVIEW PROCESS	7-9

<u>Section</u>		<u>Page</u>
<b>8.0</b>	<b><u>DRAINAGE DESIGN CRITERIA FOR RURAL SUBDIVISIONS</u></b>	8-1
8.1	PURPOSE	8-1
8.2	QUALIFICATIONS	8-1
8.3	DESIGN CRITERIA	8-2
8.4	SUBMITTALS	8-2
8.5	TECHNICAL ANALYSIS OF DETENTION REQUIREMENTS FOR RURAL SUBDIVISIONS	8-4
8.6	ANALYSIS OF RUNOFF VOLUME	8-5
8.7	ANALYSIS OF RUNOFF RATE	8-6
8.8	DETERMINATION OF REQUIRED DETENTION	8-7
<b>9.0</b>	<b><u>REFERENCES</u></b>	9-1
Appendix A	Development of Hydrologic Methodology for Fort Bend County, Texas	
Appendix B	Texas Administrative Code Chapter 299 – Dams and Reservoirs	
Appendix C	Development of Pump Station Design Criteria for Fort Bend County, Texas	

## **LIST OF TABLES**

- 2-1 Point Rainfall Amounts for Varying Durations and Frequencies in Fort Bend County, Texas
- 2-2 Typical Average Values for Impervious Cover
- 2-3 Rational Method Runoff Coefficients for 5-10 year Frequency Storms
- 2-4 Frequency Factor Adjustment
- 2-5 Excess Rainfall for Computing Runoff Volumes
- 3-1 Values of the Manning's Roughness Coefficient (n)
- 3-2 Computation of Composite Roughness Coefficient for Excavated and Natural Channels
- 3-3 Allowable 25-year Velocities for Channel Design
- 3-4 Right-of-Way Requirements for Fort Bend County, Texas
- 4-1 Headwall Guidelines
- 4-2 Inlet Loss Coefficients Used for Culverts Flowing with Outlet Control
- 5-1 Rainfall Runoff Curves for Fort Bend County
- 5-2 Values of the Manning's Roughness Coefficient (n) for Corrugated Metal Pipes
- 5-3 Coefficients at Structures
- 5-4 Coefficients for Entrance Losses
- 6-1 Minimum Detention Requirements for Drainage Areas Less Than 50 Acres

## **LIST OF FIGURES**

- 2-1 Effect of Watershed Development on Storm Hydrograph
- 2-2 Ponding Adjustment Factor for Clarks Storage Coefficient (R) for Fort Bend County, Texas
- 2-3 Example of Watershed for Determination of Basin Physical Parameters
- 2-4 25-Year Drainage Area – Discharge Curves for Fort Bend County, Texas
- 2-5 100-Year Drainage Area – Discharge Curves for Fort Bend County, Texas
- 2-6 Average Velocities for Estimating Travel Time for Overland Flow for Fort Bend County, Texas
- 2-7 Rainfall Intensity/Duration Curves for Fort Bend County, Texas
- 2-8 Malcom's Method of Hydrograph Development
- 3-1 Nomograph for Solution of Manning's Equation
- 3-2 Nomograph for Solution of Uniform Flow in Trapezoidal Channels

## **LIST OF FIGURES (Continued)**

- 3-3 Required Erosion Protection at Channel Confluence
- 3-4 Typical Backslope Drain Detail for Fort Bend County, Texas
- 3-5 Typical Storm Sewer Outfall Detail Fort Bend County, Texas
- 3-6 Typical Bent Detail for C.G.M.P. Outfall for Fort Bend County, Texas
- 3-7 Typical Bedding and Backfill Detail for C.G.M.P. Outfall for Fort Bend County, Texas
- 3-8 Recommend Baffle Pier Heights and Allowable Velocities
- 3-9 Baffled Chute Typical Detail
- 4-1 Hydraulic Elements of Flow Through a Culvert
- 5-1 Storm Sewer – Channel Interaction for Fort Bend County, Texas
- 5-2 Rainfall Runoff Curves for Fort Bend County, Texas
- 5-3 Undesirable Sheet Flow Patterns for Fort Bend County, Texas
- 5-4 Acceptable Sheet Flow Patterns for Fort Bend County, Texas
- 5-5 Typical Roadside Ditch Drain Detail for Fort Bend County, Texas
- 6-1 Minimum Detention Requirements for Drainage Areas Less Than 50 Acres
- 7-1-1 – 7-1-16 Brazos River Water Surface Profiles for Fort Bend County, Texas
- 7-2 Flow/Frequency for Fort Bend County, Texas
- 7-3 Rainfall/Frequency for Fort Bend County, Texas
- 8-1 Detention Storage Requirements for Rural Subdivisions
- 8-2 Comparison of Different Storage Requirements